

References (SSVEP-Based BCI)

- Allison B.Z., McFarland D.J., Schalk G., Zheng S.D., Jackson M.M., Wolpaw J.R., Towards an independent brain-computer interface using steady state visual evoked potentials, *Clin Neurophysiol*, 2008, 119(2):399-408.
- Allison BZ, Brunner C, Kaiser V, Müller-Putz GR, Neuper C, Pfurtscheller G, Toward a hybrid brain-computer interface based on imagined movement and visual attention, *J Neural Eng*. 2010 Apr;7(2):26007.
- Allison B, Luth T, Valbuena D, Teymourian A, Volosyak I, Graser A, BCI demographics: how many (and what kinds of) people can use an SSVEP BCI?, *IEEE Trans Neural Syst Rehabil Eng*. 2010 Apr;18(2):107-16.
- Bakardjian H., Martinez P., Cichocki A., Dynamic Online Target Control of SSVEP-Based Brain-Computer Interface with Multiple Commands, *Neuroscience Research* 2007; 58(Suppl 1):S70.
- Bakardjian H., Martinez P., Cichocki A., Steady-state visual evoked responses as a reliable tool for an online 8-command brain-machine interface, *Proc. of World Multi-Conference on Systemics, Cybernetics and Informatics (WMSCI'08)*, 2008.
- Bakardjian H, Tanaka T, Cichocki A, Optimization of SSVEP brain responses with application to eight-command Brain-Computer Interface, *Neurosci Lett*, 2010, 469(1):34-38.
- Bakardjian H, Tanaka T, Cichocki A, Brain Control of Robotic Arm Using Affective Steady-State Visual Evoked Potentials, *IASTED International Conference on Human-Computer Interaction (IASTED-HCI 2010)*, p.264-270.
- Cheng M, Gao X, Gao S, Xu D., Design and implementation of a brain-computer interface with high transfer rates, *IEEE Trans Biomed Eng*. 2002, 49(10):1181-1186.
- Friman O, Volosyak I, Graser A, Multiple channel detection of steady-state visual evoked potentials for brain-computer interfaces, *IEEE Trans Biomed Eng*. 2007; 54(4):742-50.
- Gao X, Xu D, Cheng M, Gao S., A BCI-based environmental controller for the motion-disabled, *IEEE Trans Neural Syst Rehabil Eng*. 2003; 11(2):137-40.
- Gollee H, Volosyak I, McLachlan AJ, Hunt KJ, Gräser A, An SSVEP-based brain-computer interface for the control of functional electrical stimulation, *IEEE Trans Biomed Eng*. 2010 Aug;57(8):1847-55.
- Grave de Peralta R, Noirhomme Q, Gonzalez Andino SL. A high-performance Brain Computer Interface based on visual attention. *Clin Neurophysiol* 2008; 119(9):e166-e167.

- Jones KS, Middendorf MS, Calhoun GL, McMillan GR, Evaluation of an electroencephalographic-based control device, Proc. 42nd Annu. Meeting of the Human Factors and Ergonom. Soc. 1998, pp.491–495.
- Sutter, E. E., The visual evoked response as a communication channel, Proc. of the IEEE / NSF Symp. on Biosensors, 1984, pp. 95-100.
- Lalor EC, Kelly SP, Finucane C, Burke R, Reilly RB, McDarby G, Brain-computer interface based on the steady-state VEP for immersive gaming control, Biomed. Tech., 2004, 49:63–64.
- Kelly SP, Lalor E, Finucane C, Reilly RB. A comparison of covert and overt attention as a control option in a steady-state visual evoked potential-based brain computer interface. Conf Proc IEEE Eng Med Biol Soc. 2004; 7:4725-8.
- Kelly SP, Lalor EC, Finucane C, McDarby G, Reilly RB. Visual spatial attention control in an independent brain-computer interface. IEEE Trans Biomed Eng. 2005a; 52(9):1588-96.
- Kelly SP, Lalor EC, Reilly RB, Foxe JJ. Visual spatial attention tracking using high-density SSVEP data for independent brain-computer communication. IEEE Trans Neural Syst Rehabil Eng. 2005b; 13(2):172-8.
- Martinez P., Bakardjian H., Cichocki A., Fully-Online, Multi-Command Brain Computer Interface with Visual Neurofeedback Using SSVEP Paradigm, J of Comp Intell and Neurosci, 2007, online article ID 94561
- Martinez P., Bakardjian H., Cichocki A., Multi-command Real-time Brain Machine Interface Using SSVEP: Feasibility Study for Occipital and Forehead Sensor Locations, Advances in Cognitive Neurodynamics - Proceedings of the International Conference on Cognitive Neurodynamics - 2007, Eds: Wang, R.; Gu, F.; Shen, E., 2008, Springer, pp.783-6
- Martinez P., Bakardjian H., Vallverdu M., Cichocki A., Fast Multi-Command SSVEP Brain Machine Interface without training, Proc. of Intern. Conf. on Artificial Neural Networks (ICANN2008), 2008.
- Materka A, Byczuk M. Alternate half-field stimulation technique for SSVEP-based brain-computer interfaces. Electronics Letters 2006, 42(6):321- 322.
- McMillan GR, Calhoun GL. Direct brain interface utilizing self-regulation of steady-state visual evoked response (SSVER), Proc RESNA Ann Conf 1995, 15:693-695.
- Middendorf M, McMillan G, Calhoun G, Jones KS. Brain-computer interfaces based on the steady-state visual-evoked response. IEEE Trans Rehabil Eng. 2000, 8(2):211-4.
- Müller MM, Hillyard SA. Concurrent recording of steady-state and transient event-related potentials as indices of visual-spatial selective attention. Clin Neurophysiol. 2000 Sep;111(9):1544-52.

- Müller-Putz GR, Scherer R, Brauneis C, Pfurtscheller G, Steady-state visual evoked potential (SSVEP)-based communication: impact of harmonic frequency components, *J Neural Eng.* 2005 Dec;2(4):123-30.
- Müller-Putz GR, Eder E, Wriessnegger SC, Pfurtscheller G. Comparison of DFT and lock-in amplifier features and search for optimal electrode positions in SSVEP-based BCI. *J Neurosci Methods.* 2008; 168(1):174-81.
- Nielsen KD, Cabrera AF, do Nascimento OF, EEG based BCI-towards a better control. Brain-computer interface research at Aalborg University. *IEEE Trans Neural Syst Rehabil Eng.* 2006; 14(2):202-4.
- Oehler M, Neumann P, Becker M, Curio G, Schilling M., Extraction of SSVEP signals of a capacitive EEG helmet for human machine interface, *Conf Proc IEEE Eng Med Biol Soc.* 2008;1:4495-8.
- Ogawa Y, Ushiba J, Tomita Y, Masakado Y, Kimura A, Liu M. Development of Brain-Computer Interface using Visual Evoked Potential. *Proc. of Meeting of Japan Neuroscience Society*, 2008.
- Pfurtscheller G, Allison BZ, Brunner C, Bauernfeind G, Solis-Escalante T, Scherer R, Zander TO, Mueller-Putz G, Neuper C, Birbaumer N, The Hybrid BCI, *Front Neurosci.* 2010 Apr 21;4:42.
- Shyu KK, Lee PL, Liu YJ, Sie JJ, Dual-frequency steady-state visual evoked potential for brain computer interface, *Neurosci Lett.* 2010 Oct 8;483(1):28-31.
- Teymourian A, Lueth T, Gräser A, Felzer T, Nordmann R. Brain-controlled finite state machine for wheelchair navigation. *Proc of 10th Intern ACM SIGACCESS Conf on Comp and Access.* 2008.
- Trejo LJ, Rosipal R, Matthews B. Brain-computer interfaces for 1-D and 2-D cursor control: designs using volitional control of the EEG spectrum or steady-state visual evoked potentials. *IEEE Trans Neural Syst Rehabil Eng.* 2006; 14(2):225-9.
- Yoshimura N, Itakura N. Study on transient VEP-based brain-computer interface using non-direct gazed visual stimuli. *Electromyogr Clin Neurophysiol.* 2008; 48(1):43-51.
- Zhu D, Bieger J, Garcia Molina G, Aarts RM, A survey of stimulation methods used in SSVEP-based BCIs, *Comput Intell Neurosci.* 2010:702357.